

CLAIM AMENDMENTS

1. (canceled).
2. (currently amended): Apparatus according to claim ~~1~~ 24 wherein said cannula permits delivery of an instrument to a surgical site.
3. (currently amended): Apparatus according to claim ~~1~~ 24 wherein the porosity of said coronary artery filter is different from the porosity of said aortic filter.
4. (currently amended): Apparatus according to claim ~~1~~ 24 wherein said coronary artery filter has a larger mesh size than said aortic filter.
5. (currently amended): Apparatus according to claim ~~1~~ 24 wherein said apparatus is configurable to form a substantial seal with a vascular structure.

6. (currently amended): Apparatus according to claim 5 wherein ~~said~~ the vascular structure is an inner surface of an aorta.

7. (currently amended): Apparatus according to claim ~~4~~ 24 further comprising at least one impermeable membrane extending longitudinally along a surface of said coronary artery filter.

8. (currently amended): Apparatus according to claim 7 wherein said at least one impermeable membrane ~~has~~ is provided with a proximal end and a distal end in an orientation corresponding to ~~said~~ the proximal end of said cannula and ~~said~~ the distal end of said cannula, respectively, and ~~said~~ the proximal end of said at least one impermeable membrane is connected to said coronary artery filter so as to channel blood flow to a coronary artery during diastole.

9. (currently amended): Apparatus according to claim ~~4~~ 24 wherein said coronary artery filter forms a perfusion conduit on a surface thereof so as to allow blood flow to a coronary artery during diastole.

10. (currently amended): Apparatus according to claim 9 further comprising an impermeable membrane extending longitudinally along a surface of said coronary artery filter, wherein said impermeable membrane having a proximal end and a distal end in an orientation corresponding to ~~said~~ the proximal end of said cannula and ~~said~~ the distal end of said cannula, respectively, and ~~said~~ the proximal end of said impermeable membrane is connected to said coronary artery filter so as to channel blood flow to ~~said~~ the coronary arteries during diastole.

11. (currently amended): Apparatus according to claim 10 wherein said apparatus is configurable to form a substantial seal with an aorta, with ~~said~~ an outer surface of said coronary artery filter leaving ~~said~~ the perfusion conduit unobstructed.

12. (withdrawn): Apparatus for performing beating heart surgery according to claim 1 further comprising at least one conduit having a proximal end and a distal end in an orientation corresponding to said proximal end of said cannula and said distal end of said cannula, respectively, said proximal end of said at least one conduit being positionable to said proximal

side of said aortic filter, and said distal end of said at least one conduit being positionable to coronary arteries.

13. (withdrawn): Apparatus for performing beating heart surgery, said apparatus comprising:

a cannula having a proximal end and a distal end;

an aortic filter in connection with said cannula, said aortic filter having a proximal side and a distal side;

a check valve in connection with said cannula, said check valve disposed on said distal side of said aortic filter; and

an impermeable membrane in connection with said cannula, said impermeable membrane having a proximal end and a distal end, and said distal end of said impermeable membrane extending beyond said distal end of said cannula in a direction from said proximal end of said cannula to said distal end of said cannula.

14. (withdrawn): Apparatus according to claim 13 wherein said cannula permits delivery of an instrument to a surgical site.

15. (withdrawn): Apparatus according to claim 13 wherein said aortic filter and said impermeable membrane define a

passageway on an outer surface thereof so as to allow blood flow to coronary arteries during diastole.

16. (withdrawn): Apparatus according to claim 15 wherein said distal end of said impermeable membrane is adapted to make a sealing engagement with a periphery of an aortic valve.

17. (withdrawn): Apparatus for performing beating heart surgery, said apparatus comprising:

a cannula having a proximal end and a distal end; and

a filter in connection with said cannula, said filter having a proximal end and a distal end, said distal end of said filter extending beyond said distal end of said cannula in a direction from said proximal end to said distal end of said cannula;

wherein said distal end of said filter is adapted to make a sealing engagement with a periphery of an aortic valve.

18. (withdrawn): Apparatus according to claim 17 wherein said cannula permits delivery of an instrument to a surgical site.

19. (canceled)

20. (withdrawn): A method for performing beating heart surgery, said method comprising:

providing apparatus for performing beating heart surgery comprising:

a cannula having a proximal end and a distal end;

an aortic filter in connection with said cannula, said aortic filter having a proximal side and a distal side;

a check valve in connection with said cannula, said check valve disposed on said distal side of said aortic filter;

a coronary artery filter in connection with said cannula, said coronary artery filter having a proximal end and a distal end, and said distal end of said coronary artery filter extending distally away from said distal end of said cannula;

said coronary artery filter comprising a perfusion conduit on an outer surface thereof so as to allow blood flow to said coronary arteries during diastole; and

deploying said apparatus in an aorta;

performing a procedure on the aortic valve; and

removing said apparatus from the aorta.

21. (withdrawn): A method for performing beating heart surgery, said method comprising:

providing apparatus for performing beating heart surgery comprising:

a cannula having a proximal end and a distal end, and said cannula configured for deployment in an aorta to allow downstream blood flow during systole in a direction from said distal end to said proximal end thereof;

an aortic filter in connection with said cannula, said aortic filter having a proximal side and a distal side;

a check valve in connection with said cannula, said check valve disposed on said distal side of said aortic filter; and

an impermeable membrane in connection with said cannula, said impermeable membrane having a proximal end and a distal end, said distal end of said impermeable membrane configured for deployment a given distance upstream of said proximal end of said proximal end of said impermeable membrane, and said distal end of said impermeable membrane extending beyond said distal end of said cannula in a direction from said proximal end of said cannula to said distal end of said cannula;

deploying said apparatus in an aorta;

performing a procedure on the aortic valve; and
removing said apparatus from the aorta.

22. (withdrawn): A method for performing beating heart surgery, said method comprising:

providing apparatus for performing beating heart surgery comprising:

a cannula having a proximal end and a distal end;

an aortic filter in connection with said cannula, said aortic filter having a proximal side and a distal side;

a check valve in connection with said cannula, said check valve disposed on said distal side of said aortic filter;

a coronary artery filter in connection with said cannula, said coronary artery filter having a proximal end and a distal end, and said distal end of said coronary artery filter extending distally away from said distal end of said cannula; and

at least one conduit having a proximal end and a distal end in an orientation corresponding to said proximal end of said cannula and said distal end of said cannula, respectively, said proximal end of said at least one conduit being positionable to said proximal side of said aortic filter, and said distal end of

said at least one conduit being positionable into a coronary artery;

deploying said apparatus in an aorta;
performing a procedure on the aortic valve; and
removing said apparatus from the aorta.

23. (canceled)

24. (new): Apparatus for performing beating heart surgery, said apparatus comprising:

a cannula having a proximal end and a distal end, the distal end of said cannula configured for deployment substantially concentrically in an aorta to allow blood flow during systole in a direction proximally from the distal end to the proximal end of said cannula;

an aortic filter mounted on a distal end portion of said cannula for disposition in the aorta;

a check valve mounted on the distal end portion of said cannula and disposed distally of said aortic filter mounted on the distal end portion of said cannula; and

a coronary artery filter connected to said cannula and extending distally of said check valve, a distal portion of said

coronary artery filter being configured for deployment upstream of said aortic filter check valve, and said coronary artery filter being configured to make a sealing engagement with a periphery of an aortic valve and cover openings into coronary arteries.

Claim 25 (new): A method for performing beating heart surgery, said method comprising:

providing apparatus comprising:

a cannula having a proximal end and a distal end, the distal end of said cannula configured for deployment substantially concentrically in an aorta to allow blood flow during systole in a direction proximally from the distal end to the proximal end of the cannula;

an aortic filter mounted on a distal end portion of the cannula for disposition in the aorta;

a check valve mounted on the distal end portion of said cannula and disposed distally of the aortic filter mounted on the distal end portion of said cannula; and

a coronary artery filter connected to the cannula, and extending distally of the check valve, a distal portion of the coronary artery filter being configured for deployment upstream

of the aortic filter, and extending distally from the distal end of the cannula, the coronary artery filter being configured to cover openings into coronary arteries adjacent a periphery of an aortic valve;

deploying the apparatus in an aorta;

performing a procedure on the aortic valve; and

removing the apparatus from the aorta.

26. (new): A method for performing beating heart surgery, said method comprising:

providing apparatus comprising:

a cannula having a proximal end and a distal end, the distal end of said cannula being configured for deployment substantially concentrically in an aorta to allow blood flow during systole in a direction proximally from the distal end to the proximal end thereof; and

a filter mounted on a distal portion of the cannula, the filter having a proximal end and a distal end, the distal end of the filter extending in a direction away from the distal end of the cannula;

wherein the filter is adapted to make a sealing engagement with a periphery of an aortic valve, and is adapted to cover openings extending into coronary arteries;

deploying the apparatus in an aorta;

performing a procedure on the aortic valve; and

removing said apparatus from the aorta.